

View Online at <https://aerobasegroup.com/nsn/5905-01-244-4452>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-25.0 to 25.0

**Electrical Resistance:**

27.000 kilohms

**Resistance Tolerance In Percent:**

-0.100 to 0.100

**Ambient Temperature In Deg Celsius At Full Rated Power:**

125.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

175.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0 to 175.0

**Inclosure Method:**

Encapsulated

**Terminal Type:**

Wire lead

**Mil-std-1276 Wire Lead Type Designator:**

C

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

0.001

**Terminal Length:**

1.500 inches

**Body Diameter:**

0.109 inches

**Body Length:**

0.250 inches

**Power Dissipation Rating In Watts:**

0.100 free air

**End Application:**

Bric test set

**Unpackaged Unit Weight:**

0.3 grams

**Style Designator:**

Axial terminal each end

**Test Data Document:**

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-r-55182/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A001a0