

View Online at <https://aerobasegroup.com/nsn/5905-01-245-3380>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Shaft Diameter:

0.375 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.594 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

End Application:

An/tsc-99

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

1.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0