## NSN 5905-01-245-4581

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-245-4581

Section Quantity:					
1					
Body Style:					
Rectangular bushing mounted					
Reliability Indicator:					
Not established					
Mounting Bushing Length:					
0.250 inches					
Body Length:					
1.344 inches					
Body Width:					
0.406 inches					
Body Height:					
0.438 inches					
Actuator Type:					
Flush drive with slot-hole					
Screw Thread Diameter:					
0.216 inches					
Screw Thread Series Designator:					
Unf					
Screw Thready Qty Per Inch (tpi):					
28.0					
Terminal Location:					
Lower adjacent side single row					
Mounting Method:					
Standard bushing					
Electrical Resistance Per Section:					
50.0 kilohms single section					
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:					
150.0 single section					
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:					
-100.0/+100.0 single section					
Power Dissipation Rating Per Section In Watts:					
0.75 free air single section					
Resistance Tolerance Per Section In Percent:					
-10.0/+10.0 single section					
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:					
85.0 single section					
Terminal Type And Quantity:					
3 wire loop					
Shelf Life:					
N/a					

## NSN 5905-01-245-4581

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



	• -			
In	ıŧ	( )t	Measure	•

--

Demilitarization:

No

Fiig:

A002a0