NSN 5905-01-245-6401

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-245-6401

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: 100.0/+100.0 Electrical Resistance: 33.000 kilohms Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width: 0.270 inches
Electrical Resistance: 33.000 kilohms Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.030 inches Body Width:
Resistance Tolerance In Percent: -2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.0830 inches Body Width:
Resistance Tolerance In Percent: 2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 125.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Inclosure Method: Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Encapsulated Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Terminal Quantity: 16 Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Terminal Type: Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Tab, solder lug Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Reliability Indicator: Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Not established Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
Terminal Length: 0.135 inches Body Length: 0.830 inches Body Width:
D.135 inches Body Length: D.830 inches Body Width:
Body Length: 0.830 inches Body Width:
0.830 inches Body Width:
Body Width:
·
0.270 inches
Body Height:
0.135 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
1.500 total network
Terminal Width:
Terminal Width:
Terminal Width: 0.022 inches
Terminal Width: 0.022 inches dentical Value Resistor Quantity:
Terminal Width: 0.022 inches Identical Value Resistor Quantity: 15 each resistor
Terminal Width: 0.022 inches Identical Value Resistor Quantity: 15 each resistor Unpackaged Unit Weight:
Terminal Width: 0.022 inches Identical Value Resistor Quantity: 15 each resistor Unpackaged Unit Weight: 1.5 grams

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-245-6401

Film Fixed Resistor Network - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0