

View Online at <https://aerobasegroup.com/nsn/5905-01-245-6410>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.780 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.500 inches

Body Length:

0.475 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.25 inch-ounces

Maximum Running Torque:

0.25 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.001 inches

Pilot Diameter Runout:

0.00250 inches

Shaft Radial Play:

0.003 inches

Mechanical Backlash In Deg Angular Rotation:

0.1

Terminal Location:

Rear end

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-500.0/+5.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0