

View Online at <https://aerobasegroup.com/nsn/5905-01-246-0395>

**Section Quantity:**

1

**Body Style:**

Rectangular w/bushing

**Reliability Indicator:**

Not established

**Mounting Bushing Length:**

Between 0.240 inches and 0.260 inches

**Body Length:**

Between 0.420 inches and 0.440 inches

**Body Width:**

Between 0.230 inches and 0.250 inches

**Body Height:**

Between 0.450 inches and 0.470 inches

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Recessed drive with slot

**Effective Electrical Rotation In Deg Angular Rotation:**

7920.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

5.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.190 inches

**Screw Thread Series Designator:**

Unf

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

200.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

7920.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0