## NSN 5905-01-246-4964

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-246-4964

| view offilite at https://aerobasegroup.com/hish/0300-01-240-4304   |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -5.0/+5.0 first temp coefficient   |
| Electrical Resistance:   |
| 46.400 kilohms   |
| Resistance Tolerance In Percent:   |
| -0.100/+0.100  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 125.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 175.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+125.0 temp range of first temp coefficient  |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Mil-std-1276 Wire Lead Type Designator:  |
| C  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.010  |
| Terminal Length:   |
| 1.905 inches   |
| Body Length:   |
| 0.310 inches   |
| Body Width:  |
| 0.320 inches   |
| Body Height:   |
| 0.110 inches   |
| Power Dissipation Rating In Watts:   |
| 0.300 free air   |
| Cubic Measure (non-core):  |
| 0.013 cubic inches   |
| Unpackaged Unit Weight:  |
| 1.0 grams  |
| Test Data Document:  |
| 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-55182/9 government specification   |

N/a

Shelf Life:

## NSN 5905-01-246-4964

Film Fixed Resistor - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A001a0