NSN 5905-01-248-1886

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-248-1886 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.484 inches **Body Width:** 0.500 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 265.0 **Maximum Starting Torque:** 4.50 inch-ounces **Maximum Running Torque:** 4.50 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **End Application:** Navy equip

Navy equip

Screw Thread Diameter:
0.250 inches

Screw Thread Series Designator:
Unef

Screw Thready Qty Per Inch (tpi):
32.0

Terminal Location:
Lower adjacent side single row

Mounting Method:

Standard bushing

NSN 5905-01-248-1886

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0