Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-248-8354

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Body Length:

0.177 inches

Body Width:

0.354 inches

Body Height:

0.433 inches

Actuator Type:

Integral knob

Effective Electrical Rotation In Deg Angular Rotation:

240.0

Maximum Starting Torque:

4.86 inch-ounces

Maximum Running Torque:

4.86 inch-ounces

Maximum Stop Torque:

13.90 inch-ounces

End Application:

6625-01-115-0395 test set, semiconductor device

Terminal Location:

Rear end

Mounting Method:

Terminal

Cubic Measure:

0.006 cubic inches

Electrical Resistance Per Section:

500.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

260.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0