NSN 5905-01-248-8355

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-248-8355

Ocation Oceantity
Section Quantity:
Body Style:
Rectangular Patrability to the stage of the
Reliability Indicator:
Not established
Body Length:
0.177 inches
Body Width:
0.354 inches
Body Height:
0.433 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Maximum Starting Torque:
4.86 inch-ounces
Maximum Running Torque:
4.86 inch-ounces
Maximum Stop Torque:
13.90 inch-ounces
End Application:
6625-01-115-0395 test set, semiconductor device
Terminal Location:
Rear end
Mounting Method:
Terminal
Cubic Measure:
0.006 cubic inches
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops

NSN 5905-01-248-8355

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature in Deg Ceisius Per Section At Full Rated Po
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0