NSN 5905-01-248-8356

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-248-8356

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
0.177 inches
Body Width:
0.354 inches
Body Height:
0.433 inches
Actuator Type:
Integral knob
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Maximum Starting Torque:
4.86 inch-ounces
Maximum Running Torque:
4.86 inch-ounces
Maximum Stop Torque:
13.90 inch-ounces
End Application:
6625-01-115-0395 test set, semiconductor device
Terminal Location:
Rear end
Mounting Method:
Terminal
Cubic Measure:
0.006 cubic inches
Electrical Resistance Per Section:
5.000 megohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-350.0/+350.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section

NSN 5905-01-248-8356

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Actuator Travel Control Feature:	
Stops	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Standard Taper Curve Per Section:	
A single section	
Terminal Type And Quantity:	
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	