## NSN 5905-01-248-9606

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-248-9606 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.562 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.312 inches **Body Length:** 0.750 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 36.00 inch-ounces **Shaft End Play:** 0.01000 inches **Shaft Runout:** 0.002 inches **Lateral Runout:** 

Pilot Diameter Runout:

0.004 inches

0.00400 inches

## NSN 5905-01-248-9606

Precision Wire Wound Variable Resistor - Page 2 of 3



Shaft Radial Play:
0.002 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.20/+0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Feat
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Special Features:
Item must comply with requirements of the defense supply center columbus production standard number lo3626; for navy nuclear propulsion
plant
Terminal Type And Quantity:
3 tab, solder lug
Reference Number Differentiating Characteristics:

Reference number differentiating material will be iaw navicp, hx quality control, mfgr and testing specs available at dla icp

N/a

Shelf Life:

## NSN 5905-01-248-9606

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0