

View Online at https://aerobasegroup.com/nsn/5905-01-248-9606

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.562 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.312 inches

Body Length:

0.750 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.80 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Maximum Stop Torque:

36.00 inch-ounces

Shaft End Play:

0.01000 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.004 inches

Pilot Diameter Runout:

0.00400 inches



Shaft Radial Play:	
Screw Thread Diameter:	
0.375 inches	
Screw Thread Series Designator:	
Unef	
Screw Thready Qty Per Inch (tpi):	
32.0 Terminal Location:	
Longitudinally positioned on the circumference	
Mounting Method: Standard bushing	
Electrical Resistance Per Section:	
5.000 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
3600.0	
Function Conformity Tolerance Per Section:	
-0.20/+0.20 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
125.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
-3.0/+3.0 single section	
Actuator Travel Control Feature:	
Stops	
Criticality Code Justification:	
Feat	
Function Characteristic Per Section:	
Single section linear	
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:	
-20.0/+20.0 single section	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Special Features:	
Item must comply with requirements of the defense supply center columbus production standard number lo3626; for navy nuclear propulsion	
plant	
Terminal Type And Quantity:	
3 tab, solder lug	
Reference Number Differentiating Characteristics:	
Reference number differentiating material will be iaw navicp, hx quality control, mfgr and testing specs available at dla icp	
Shelf Life:	

Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0