Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-249-4682

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

Electrical Resistance:

2.000 kilohms

Resistance Tolerance In Percent:

-2.000/+2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

Inclosure Method:

Encapsulated

Terminal Quantity:

8

Terminal Type:

Pin

Reliability Indicator:

Not established

Terminal Length:

0.135 inches

Body Length:

0.783 inches

Body Width:

0.074 inches

Body Height:

0.187 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

0.840 total network

Identical Value Resistor Quantity:

7 each resistor

Special Features:

Nuclear hardness critical items

Nuclear Hardness Critical Feature:

Hardened

Unpackaged Unit Weight:

1.5 grams

Style Designator:

Single inline

NSN 5905-01-249-4682

Film Fixed Resistor Network - Page 2 of 2



Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0