## NSN 5905-01-249-5740

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-249-5740

| Towns and the Confliction of Projector of the Post Res Post College |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:       |
| -30.0/+30.0   |
| Electrical Resistance:  |
| 20.000 ohms   |
| Resistance Tolerance In Percent:                                    |
| -1.000/+1.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:             |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:     |
| 275.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:        |
| -55.0/+275.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 1.375 inches and 1.625 inches                               |
| Body Diameter:  |
| Between 0.063 inches and 0.093 inches                               |
| Body Length:  |
| Between 0.235 inches and 0.265 inches                               |
| Power Dissipation Rating In Watts:                                  |
| 1.000 free air  |
| Cubic Measure (non-core):   |
| 0.002 cubic inches  |
| Unpackaged Unit Weight:   |
| 0.2 grams   |
| Style Designator:   |
| Axial terminal each end   |
| Specification Data:   |
| 07482-j350 manufacturers source control                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| _   |
| Demilitarization:   |
| No  |
| Fiig:   |

A001a0