## NSN 5905-01-249-7004

-50.0/+50.0

**Electrical Resistance:** 

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-249-7004

**Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:** 

| 4.750 onins  |
|--|
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+275.0   |
| Inclosure Method:  |
| Encased  |
| Terminal Type:   |
| Wire loop  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 0.312 inches   |
| Body Diameter:   |
| 0.500 inches   |
| Mounting Bushing Length:   |
| 0.250 inches   |
| Body Length:   |
| 0.500 inches   |
| Power Dissipation Rating In Watts:   |
| 5.000 free air   |
| Mounting Bushing Diameter:   |
| 0.375 inches   |
| Cubic Measure (non-core):  |
| 0.150 cubic inches   |
| Unpackaged Unit Weight:  |
| 6.0 grams  |
| Style Designator:  |
| Axial terminals one end  |
| Test Data Document:  |
| 26512-gr815ed drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                              |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
|  |

## NSN 5905-01-249-7004

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0