NSN 5905-01-250-2485

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-250-2485

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.200 inches |
| Shaft Diameter: |
| 0.090 inches |
| Shaft Length: |
| 0.060 inches |
| Body Length: |
| 0.395 inches |
| Body Width: |
| 0.240 inches |
| Body Height: |
| 0.375 inches |
| Shaft Style: |
| Round, slotted |
| Actuator Type: |
| Single shaft |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 9000.0 |
| Maximum Starting Torque: |
| 3.00 inch-ounces |
| Maximum Running Torque: |
| 3.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| 0.200 inches |
| Terminal Location: |
| Rear end |
| Mounting Method: |
| Terminal |
| Electrical Resistance Per Section: |
| 1.000 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 9000.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| 0.100 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |

125.0 single section

NSN 5905-01-250-2485

Demilitarization:

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:**