Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-250-3287

| Section Quantity: | |
|--|--|
| 1 | |
| Body Style: | |
| Rectangular | |
| Reliability Indicator: | |
| Established | |
| Reliability Failure Rate Level In Percent: | |
| 0.010 | |
| Terminal Length: | |
| 0.172 inches | |
| Shaft Diameter: | |
| 0.075 inches | |
| Shaft Length: | |
| 0.050 inches | |
| Body Length: | |
| 0.250 inches | |
| Body Width: | |
| 0.165 inches | |
| Body Height: | |
| 0.250 inches | |
| Shaft Style: | |
| Round, slotted | |
| Shaft Bearing Type: | |
| Sleeve | |
| Actuator Type: | |
| Single shaft | |
| Effective Electrical Rotation In Deg Angular Rotation: | |
| Between 3600.0 and 9000.0 | |
| Maximum Starting Torque: | |
| 3.00 inch-ounces | |
| Maximum Running Torque: | |
| 3.00 inch-ounces | |
| Center To Center Distance Between Terminals: | |
| 0.200 inches | |
| Terminal Location: | |
| Left adjacent side two rows | |
| Mounting Method: | |
| Terminal | |
| Center To Center Distance Between Terminal Rows: | |
| 0.100 inches | |
| Cubic Measure: | |
| 0.010 cubic inches | |
| | |

NSN 5905-01-250-3287

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section: 1.000 percent, rated amperes c and better flooring **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 9000.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 7th secondary quality **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section **Test Data Document:** 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-39035/3 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0