NSN 5905-01-250-9879

A001a0

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-250-9879

-50.0/+50.0 Electrical Resistance: 3.060 ohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+275.0 Tempurature Method: Encapsulated Terminal Type: Wire laad Reliability Indicator: Note stabilished Terminal Longth: 1.500 inches Body Diameter: 0.187 inches Body Jennete: 0.187 inches Body Length: 0.580 inches Power Dissipation Rating in Watts: 3.000 free air Cubic Messure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80044 Clist is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: No	computative Coefficient Of Resistance In Dam Dev Dev Coloius.
Electrical Resistance: 8.060 bms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating in Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: N/a	empurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: -0.187 inches Body Diameter: -0.187 inches Body Length: -0.500 inches Tower Dissipation Rating in Watts: -0.3000 free air Cubic Measure (non-core): -0.015 cubic inches Unpackaged Unit Weight: -0.400 grams Style Designator: -0.418 terminal each end Test Data Document: -0.249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; -0.540 if Life: No	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -5.5.0/275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 020429-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na	
-1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: Axia I terminal each end Test Data Document: 0x249-7300620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55,0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Diameter: 0.560 inches Power Dissipation Rating In Watts: 3.000 riee air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730520 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Diameter: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.550 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal cach end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheft Life: N/a	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encaspulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730820 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
-55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.00 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	nclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ncapsulated
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	erminal Type:
Not established Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	/ire lead
Terminal Length: 1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	eliability Indicator:
1.500 inches Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ot established
Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	erminal Length:
Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.500 inches
Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ody Diameter:
0.560 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.187 inches
Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ody Length:
3.000 free air Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.560 inches
Cubic Measure (non-core): 0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ower Dissipation Rating In Watts:
0.015 cubic inches Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.000 free air
Unpackaged Unit Weight: 4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	ubic Measure (non-core):
4.0 grams Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.015 cubic inches
Style Designator: Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	npackaged Unit Weight:
Axial terminal each end Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	.0 grams
Test Data Document: 80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	tyle Designator:
80249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	xial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	est Data Document:
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	0249-730620 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
Shelf Life: N/a	
N/a	
Unit of Measure:	Init Of Measure:
Demilitarization:	emilitarization:
No No	
Fiig:	