Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-252-0196

#### Section Quantity:

1

Body Style:

Cylindrical servo mounted

### **Reliability Indicator:**

Not established

#### **Pilot Diameter:**

0.6250 inches

#### **Pilot Length:**

0.0620 inches

#### **Undercut Diameter:**

0.781 inches

#### **Undercut Width:**

0.0570 inches

#### **Body Diameter:**

0.875 inches

# Shaft Diameter:

Shart Diameter.

0.1248 inches

## Shaft Length:

0.375 inches

#### Body Length:

0.875 inches

#### Mounting Lip Diameter:

0.8750 inches

#### Mounting Lip Depth:

0.0620 inches

#### Shaft Style:

Round, slotted

#### Shaft Bearing Type:

Ball

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

6.00 inch-ounces

#### Maximum Running Torque:

6.00 inch-ounces

#### Shaft End Play:

0.00500 inches

#### Shaft Runout:

0.002 inches

# NSN 5905-01-252-0196

Precision Nonwire Wound Variable Resistor - Page 2 of 2

