

View Online at <https://aerobasegroup.com/nsn/5905-01-253-1442>

Electrical Resistance:

50.0 kilohms and 196.0 kilohms and 20.0 kilohms and 301.0 kilohms and 100.0 kilohms

Resistance Tolerance In Percent:

-10.0/+10.0 and -1.0/+1.0 and -10.0/+10.0 and -1.0/+1.0 and -10.0/+10.0

Terminal Quantity:

3 and 2 and 3 and 2 and 3

Terminal Type:

Wire lead and wire lead and wire lead and wire lead and wire lead

Resistor Power Dissipation Rating In Watts:

0.75 and 0.25 and 0.75 and 0.1 and 0.75

Mounting Method:

Solder

Component Quantity:

1 and 1 and 1 and 1 and 1

Component Controlling Agency:

Honeywell avionics

Component Name:

Variable nonwirewound, nonprecision resistor 1, 3, 5; fixed film resistor 2, 4

Component Identifying Number:

89ph50k part no. And rlr07c1963fr part no. And 89ph20k part no. And rnc55h3013fr part no. And 89ph100k part no.

Assembly Construction Method:

Mounted on socket

Component Relationship:

Not matched

Criticality Code Justification:

Feat

Special Features:

Esd

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T172-f