Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-253-2745

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.3750 inches

Pilot Length:

0.0620 inches

Overall Length:

1.593 inches

Undercut Diameter:

0.400 inches

Undercut Width:

0.0630 inches

Body Diameter:

0.500 inches

Shaft Diameter:

0.0935 inches

Shaft Length:

0.375 inches

Body Length:

1.178 inches

Overall Diameter:

0.844 inches

Mounting Lip Diameter:

0.5000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3620.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.30 inch-ounces



Shaft Runout: 0.003 inches Lateral Runout: 0.003 inches **Pilot Diameter Runout:** 0.00200 inches Shaft Radial Play: 0.002 inches **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 10.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** Between 3600.0 and 3620.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -15.0/+15.0 single section **Actuator Travel Control Feature:** Clutch **Function Characteristic Per Section:** Single section linear Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96214-802369 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:**

3 turret

Shelf Life:

N/a



Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0