NSN 5905-01-255-0734

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-255-0734 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 0.7500 inches Pilot Length: 0.0620 inches **Overall Length:** 1.370 inches **Undercut Diameter:** 0.781 inches **Undercut Width:** 0.0620 inches **Body Diameter:** 0.875 inches **Mounting Hole Diameter:** Between 0.152 inches and 0.157 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.500 inches **Body Length:** 1.000 inches **Overall Diameter:** 1.600 inches **Mounting Lip Diameter:** 0.8750 inches **Mounting Lip Depth:** 0.0620 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 180.0 **Maximum Starting Torque:** 20.00 inch-ounces

NSN 5905-01-255-0734

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Maximum Running Torque:
20.00 inch-ounces
Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.00100 inches
Shaft Radial Play:
0.001 inches
Mechanical Backlash In Deg Angular Rotation:
0.5
Mounting Facility Quantity:
2
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
2.0 percent, rated amperes c and better finish
Rotary Actuator Travel In Angular Deg:
180.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Power Dissipation Rating Per Section In Watts:
1.5 free air all sections
Fixed Tap Quantity Per Section:
1 1st section
Tap Location Tolerance Per Section:
Tap Location Tolerance Per Section: -5.0/+5.0 ohms 1st section
-5.0/+5.0 ohms 1st section
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent:
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature:
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms:
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 1st section
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 1st section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 1st section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 1st section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section:
-5.0/+5.0 ohms 1st section Resistance Tolerance Per Section In Percent: -5.0/+5.0 all sections Actuator Travel Control Feature: Stops Tap Location From Ccw Terminal Per Section In Ohms: 1000.0 1st section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 all sections Standard Taper Curve Per Section: A all sections

89.6 grams

NSN 5905-01-255-0734

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
7 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0