NSN 5905-01-255-3826

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-255-3826

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -100.0 to 100.0 Electrical Resistance: 82.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams Style Designator:
Electrical Resistance: 82.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.416 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
82.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
-5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 130.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 130.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Not established Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Terminal Length: Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Between 1.375 inches and 1.675 inches Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Body Diameter: Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Between 0.115 inches and 0.161 inches Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Body Length: Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Between 0.344 inches and 0.416 inches Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
Power Dissipation Rating In Watts: 0.500 free air Unpackaged Unit Weight: 0.9 grams
0.500 free air Unpackaged Unit Weight: 0.9 grams
Unpackaged Unit Weight: 0.9 grams
0.9 grams
•
Style Designator:
- ,
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0