# NSN 5905-01-255-5819

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-255-5819

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.251 inches
Body Length:
1.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
2.00 inch-ounces
Maximum Running Torque:
1.00 inch-ounces
Maximum Stop Torque:
160.00 inch-ounces
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.562 inches
Shaft End Play:
0.005 inches
Shaft Runout:
0.001 inches
Lateral Runout:
0.001 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:

0.002 inches

### NSN 5905-01-255-5819

Precision Wire Wound Variable Resistor - Page 2 of 3



#### Mechanical Backlash In Deg Angular Rotation:

0.5

**Screw Thread Diameter:** 

0.250 inches

**Screw Thread Series Designator:** 

Unef

Screw Thready Qty Per Inch (tpi):

32.0

**Terminal Location:** 

Radially positioned over less than half the circumference

**Mounting Method:** 

Standard bushing

**Electrical Resistance Per Section:** 

100.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

3600 O

**Function Conformity Tolerance Per Section:** 

-0.10/+0.10 single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-1000.0/+1000.0 single section

**Power Dissipation Rating Per Section In Watts:** 

2.0 free air single section

**Function Conformity Per Section:** 

Single section independent linearity

**Resistance Tolerance Per Section In Percent:** 

-3.0/+3.0 single section

**Actuator Travel Control Feature:** 

Stops

**Function Characteristic Per Section:** 

Single section linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Test Data Document:** 

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

3 turret

**Specification Data:** 

81349-mil-r-12934/31 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

# NSN 5905-01-255-5819

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0