## NSN 5905-01-256-1165

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-256-1165

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Cylindrical bushing mounted                               |
| Reliability Indicator:                                    |
| Not established   |
| Body Diameter:  |
| 0.750 inches  |
| Shaft Diameter:   |
| 0.125 inches  |
| Shaft Length:   |
| 0.500 inches  |
| Mounting Bushing Length:                                  |
| 0.250 inches  |
| Body Length:  |
| 0.375 inches  |
| Shaft Style:  |
| Round, slotted  |
| Actuator Type:  |
| Single shaft  |
| Effective Electrical Rotation In Deg Angular Rotation:    |
| Between 295.0 and 305.0                                   |
| Nonturn Device Location:                                  |
| At 9 oclock   |
| Nonturn Device Radius:                                    |
| 0.375 inches  |
| Screw Thread Diameter:                                    |
| 0.250 inches  |
| Screw Thread Series Designator:                           |
| Unef  |
| Screw Thready Qty Per Inch (tpi):                         |
| 32.0  |
| Terminal Location:  |
| Radially positioned over less than half the circumference |
| Mounting Method:  |
| Standard bushing  |
| Electrical Resistance Per Section:                        |
| 2.0 kilohms single section                                |
| Rotary Actuator Travel In Angular Deg:                    |
|   |

Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single section and +0.0/+3.0 120 degrees celsius single section

## NSN 5905-01-256-1165

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:   |
|---|
| 120.0 single section  |
| Power Dissipation Rating Per Section In Watts:  |
| 0.5 free air single section   |
| Resistance Tolerance Per Section In Percent:  |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:   |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |
| Test Data Document:   |
| 81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental         |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.).   |
| Terminal Type And Quantity:   |
| 3 tab, solder lug   |
| Specification Data:   |
| 81349-mil-r-94/2 government specification   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |