

View Online at <https://aerobasegroup.com/nsn/5905-01-256-2753>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.266 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 309.0 and 320.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

3.5 percent, rated amperes c and better finish

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Resistance Temperature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and +0.0/+3.0 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-r-94/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0