## NSN 5905-01-256-6716

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-256-6716  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -100.0/+100.0  |
| Electrical Resistance:   |
| 182.000 ohms   |
| Resistance Tolerance In Percent:   |
| -1.000/+1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 125.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+125.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Quantity:   |
| 16   |
| Terminal Type:   |
| Pin  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| Between 0.125 inches and 0.150 inches  |
| Body Length:   |
| 0.830 inches   |
| Body Width:  |
| Between 0.240 inches and 0.305 inches  |
| Body Height:   |
| 0.135 inches   |
| Schematic Diagram Designator:  |
| Isolated array   |
| Power Dissipation Rating In Watts:   |
| 1.600 total network  |
| Identical Value Resistor Quantity:   |
| 8 each resistor  |
| Unpackaged Unit Weight:  |
| 1.5 grams  |
| Style Designator:  |
| Dual inline  |
| Test Data Document:  |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/2 government specification

## NSN 5905-01-256-6716

Film Fixed Resistor Network - Page 2 of 2



| _  |   |   |    |    |    |
|----|---|---|----|----|----|
| ٠. | n | _ | I+ | 18 | e: |
|    |   |   |    |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0