NSN 5905-01-256-9991

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-256-9991

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0
Electrical Resistance:
191.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reactance Characteristic:
Noninductive
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
Reliability Failure Rate Level in Fercent.
0.010
0.010
0.010 Terminal Length:
0.010 Terminal Length: 0.266 inches
0.010 Terminal Length: 0.266 inches Body Length:
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width:
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height:
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
0.010 Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts:
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts: 3.000 free air
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts: 3.000 free air Terminal Width:
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts: 3.000 free air Terminal Width: 0.085 inches
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts: 3.000 free air Terminal Width: 0.085 inches Mounting Hole Size:
Terminal Length: 0.266 inches Body Length: 0.600 inches Body Width: 0.334 inches Body Height: 0.320 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.444 inches Power Dissipation Rating In Watts: 3.000 free air Terminal Width: 0.085 inches Mounting Hole Size: 0.093 inches

3.300 grams

NSN 5905-01-256-9991

Wire Wound Fixed Resistor - Page 2 of 2



~ ·					
Styl	ם ו	126	เตท	ato	ŀ۲۰
Oty:		-	ıyı,	ato	

Axial terminal (s)

Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0