## NSN 5905-01-257-6907



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-257-6907 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.469 inches **Shaft Style:** Round, slotted **Switch Voltage Rating In Volts:** 125.0 and 28.0 **Actuator Type:** 

Single shaft

**Switch Operating Position:** 

Start of rotation

**Terminal Location:** 

Rear-bottom

**Mounting Method:** 

**Terminal** 

**Features Provided:** 

Switch

**Electrical Resistance Per Section:** 

5.0 kilohms single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.5 free air single section

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Switch Current Type And Rating In Amps:** 

0.500 ac and 1.500 dc

## NSN 5905-01-257-6907

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0