

View Online at <https://aerobasegroup.com/nsn/5905-01-257-8219>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7490 inches and 0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

0.562 inches

Body Length:

0.790 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

0.481 cubic inches

Electrical Resistance Per Section:

2.800 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

360.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Fixed Tap Quantity Per Section:

3 single section

Tap Location Tolerance Per Section:

-5.0/+5.0 ohms single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Tap Location From Ccw Terminal Per Section In Ohms:

700.0 single section and 700.0 single section and 700.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

85374-277356 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0