

View Online at <https://aerobasegroup.com/nsn/5905-01-258-7578>

Electrical Resistance:

52.3 kilohms and 75.0 kilohms and 93.1 kilohms and 169.0 kilohms and 200.0 kilohms and 71.5 kilohms and 95.3 kilohms and 100.0 kilohms and 90.9 kilohms and 68.1 kilohms

Resistance Tolerance In Percent:

-1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0

Terminal Quantity:

4 and 6 and 4 and 4 and 4 and 2 and 2 and 32 and 2 and 4

Terminal Type:

Wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead

Resistor Power Dissipation Rating In Watts:

0.125 and 0.125 and 0.125 and 0.125 and 0.125 and 0.125 and 0.125 and 0.125 and 0.125 and 0.125

Mounting Method:

Solder

Component Quantity:

2 and 3 and 2 and 2 and 2 and 1 and 1 and 16 and 1 and 2

Component Controlling Agency:

Honeywell

Component Name:

Fixed film resistor

Component Identifying Number:

Rlr05c5232fp part no. And rlr05c7502fp part no. And rlr05c9312fp part no. And rlr05c1693fp part no. And rlr05c2003fp part no. And rlr05c7152fp part no. And rlr05c9532fp part no. And rlr05c1003fp part no. And rlr05c9092fp part no. And rlr05c6812fp part no.

Assembly Construction Method:

Mounted on printed circuit board

Component Relationship:

Not matched

Special Features:

P/n34059618-2 is two-way interchangeable but has two more resistor on it has rlr05c4642fp and rlr05c7872fp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T172-f