

View Online at <https://aerobasegroup.com/nsn/5905-01-258-8804>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.180 inches

Shaft Diameter:

Between 0.060 inches and 0.100 inches

Shaft Length:

Between 0.040 inches and 0.077 inches

Body Length:

Between 0.360 inches and 0.420 inches

Body Width:

0.250 inches

Body Height:

Between 0.360 inches and 0.390 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

7200.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Rear end

Mounting Method:

Terminal

Cubic Measure:

0.057 cubic inches

Electrical Resistance Per Section:

1.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

7200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0