Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-259-0006

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0

#### **Electrical Resistance:**

240.000 kilohms

# **Resistance Tolerance In Percent:**

-0.100/+0.100

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

145.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-65.0/+145.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

**Reactance Characteristic:** 

# Noninductive

**Reliability Indicator:** 

Established

# **Reliability Failure Rate Level In Percent:**

0.010

#### **Terminal Length:**

1.500 inches

### **Body Diameter:**

0.500 inches

### **Body Length:**

1.000 inches

### **Power Dissipation Rating In Watts:**

0.750 free air

### Style Designator:

Axial terminal each end

### **Test Data Document:**

81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-39005/7a government specification

#### Shelf Life:

N/a

#### Unit Of Measure:

# **Demilitarization:**

No

# NSN 5905-01-259-0006

Wire Wound Fixed Resistor - Page 2 of 2

Fiig: A001a0

