NSN 5905-01-259-0016

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-259-0016

Tompurature Coefficient Of Resistance In Dam Der Der Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-10.0/+10.0
Electrical Resistance:
1.070 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0 Tempurature Pange Of Tempurature Coefficient In Dag Calcius:
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+145.0
Inclosure Method:
Encapsulated To a second secon
Terminal Type:
Wire lead
Reactance Characteristic:
Noninductive Service S
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Terminal Length:
1.500 inches
Body Diameter:
0.250 inches
Body Length:
0.500 inches
Power Dissipation Rating In Watts:
0.150 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39005 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39005/4d government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-259-0016

Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0