

View Online at <https://aerobasegroup.com/nsn/5905-01-259-2637>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.860 inches and 0.890 inches

**Shaft Diameter:**

Between 0.2495 inches and 0.2500 inches

**Shaft Length:**

Between 0.361 inches and 0.423 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.750 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.80 inch-ounces

**Maximum Running Torque:**

0.80 inch-ounces

**Maximum Stop Torque:**

75.00 inch-ounces

**Nonturn Device Location:**

At 6 oclock

**Shaft End Play:**

0.010 inches

**Shaft Runout:**

0.003 inches

**Lateral Runout:**

0.004 inches

**Pilot Diameter Runout:**

0.004 inches

**Shaft Radial Play:**

0.002 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0