## NSN 5905-01-259-3155

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-259-3155
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.500 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.453 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 292.0 and 298.0
Nonturn Device Location:
At 4'30 oclock and at 10'30 oclock
Nonturn Device Radius:
0.245 inches
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 292.0 and 298.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-3.0/+0.0 -55 degrees celsius single section and -5.0/+10.0 -25 degrees celsius single section and -5.0/+10.0 25 degrees celsius single
section and +0.0/+3.0 120 degrees celsius single section

## NSN 5905-01-259-3155

**Fiig:** A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
31349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
31349-mil-r-94/3 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No.