

View Online at <https://aerobasegroup.com/nsn/5905-01-259-3518>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Not established

**Thread Length:**

0.375 inches

**Mounting Hole Diameter:**

0.114 inches

**Shaft Diameter:**

0.094 inches

**Shaft Length:**

1.340 inches

**Body Length:**

1.740 inches

**Body Width:**

0.330 inches

**Body Height:**

0.575 inches

**Shaft Style:**

Round, threaded

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Double ended shaft

**Longitudinal Actuator Travel:**

0.84 inches

**Longitudinal Actuator Effective Electrical Stroke Length:**

0.840 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

Harm missile assembly

**Lateral Distance Between Mounting Hole Centers:**

1.250 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Cubic Measure:**

0.413 cubic inches

**Electrical Resistance Per Section:**

2.0 kilohms single section

**Function Conformity Tolerance Per Section:**

-0.80 to 0.80 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.6 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

100.0 single section

**Special Features:**

12 inches polytetrafluoroethylene insulated leads

**Test Data Document:**

30003-704as3644 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0