

View Online at https://aerobasegroup.com/nsn/5905-01-259-3521

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.239 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.812 inches

Mounting Bushing Length:

0.420 inches

Body Length:

1.427 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Maximum Stop Torque:

75.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.290 inches

Shaft End Play:

0.010 inches

Shaft Runout:

0.002 inches



Lateral Runout:

0.005 inches

Pilot Diameter Runout:

0.003 inches

Shaft Radial Play:

0.003 inches

Fragility Factor:

Rugged

End Application:

6625-01-170-6876, ohio class ss (trident), general purpose electronic test equipment, emory s.Land class as

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

0.574 cubic inches

Electrical Resistance Per Section:

10.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 all sections

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary finish

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 all sections

Actuator Travel Control Feature:

Stops

Criticality Code Justification:

Feat

Precision Wire Wound Variable Resistor - Page 3 of 3



Function Characteristic Per Section:

All sections linear

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Special Features:

Weapons system essential

Unpackaged Unit Weight:

0.80 ounces

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0