Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-259-5021

Section Quantity:

1

Body Style:

Rectangular w/mounting holes/slots

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.000

Mounting Hole Diameter:

0.093 inches

Shaft Diameter:

0.115 inches

Shaft Length:

0.058 inches

Body Length:

1.250 inches

Body Width:

0.190 inches

Body Height:

0.315 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 6120.0 and 9720.0

Maximum Starting Torque:

8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Lateral Distance Between Mounting Hole Centers:

1.000 inches

Mounting Facility Quantity:

2

Terminal Location:

Rear end

Mounting Method:

Terminal and unthreaded hole

Cubic Measure:

0.075 cubic inches

Electrical Resistance Per Section:

200.0 percent, rated amperes c and better flooring

NSN 5905-01-259-5021 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

AeroBase Group

Rotary Actuator Travel In Angular Deg:

Between 6120.0 and 9720.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 wire lead

Specification Data:

81349-mil-r-39035/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0