## NSN 5905-01-259-5164

Inductive Wire Wound Fixed Resistor - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5905-01-259-5164
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-50.0/+50.0 first temp coefficient
Electrical Resistance:
3.160 ohms each resistor
Resistance Tolerance In Percent:
-0.500/+0.500 each resistor
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Reactance Characteristic:
Inductive
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.500 inches
Body Diameter:
0.312 inches
Body Length:
0.875 inches
Power Dissipation Rating In Watts:
5.000 free air
Cubic Measure (non-core):
0.085 cubic inches
Unpackaged Unit Weight:
5.0 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:

N/a

Shelf Life:

81349-mil-r-39007/6 government specification

## NSN 5905-01-259-5164

Inductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0