NSN 5905-01-259-5414

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-259-5414

Electrical Resistance: 33.000 ohms Resistance Tolerance in Percent: -5.000 to 5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.50 to 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -5.50 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Width: 0.075 inches Power Dissipation Rating in Watts: 0.050 free air Style Designator: Termination pad each end Tests Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) setc: excludes unit of Measure:	Tompurature Coefficient Of Resistance In Dam Der Der Calaine
Electrical Resistance: 33.000 ohms Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: -0.025 inches Body Width: -0.075 inches Body Height: -0.075 inches Body Height: -0.075 inches Power Dissipation Rating In Watts: -0.050 free air Style Designator: Termination pad each end Test Data Document: -0.384-04-135-132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -5.000 to 5.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: -0.025 inches Body Width: -0.025 inches Body Height: -0.075 inches Body Height: -0.076 inches Power Dissipation Rating In Watts: -0.050 free air Style Designator: Terminal opa deach end Test Data Document: -0.03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.:	
Resistance Tolerance in Percent: -5.000 to 5.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninciosure Method: Uninciosure Method: Uninciosure Method systyle Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Width: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 30340-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.075 inches Body Width: 0.075 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating in Watts: 0.05 free air Style Designator: Termination pad each end Test Data Document: 0.3640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosued Terminal Type: Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.025 inches Body Height: 0.076 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: Style Designator: Style Designator: standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.025 inches Body Width: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Note established Body Length: 0.025 inches Body Width: 0.025 inches Body Width: 0.050 fries air Style Designator: Terminal on pad each end Tests Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Width: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Terminalton pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0 to 125.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.025 inches Body Width: 0.075 inches Body Wight: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Uninclosed Terminal Type: Terminal Type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Terminal Type: Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	
Terminal type per body style Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Reliability Indicator: Not established Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Note stablished Body Length: 0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
0.025 inches Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Width: 0.075 inches Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.025 inches
Body Height: 0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Width:
0.010 inches Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.075 inches
Power Dissipation Rating In Watts: 0.050 free air Style Designator: Termination pad each end Test Data Document: 0.3640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.: excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.010 inches
Style Designator: Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Termination pad each end Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.050 free air
Test Data Document: 03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Termination pad each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	03640-6135132 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a Unit Of Measure: Demilitarization: No Fiig:	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0