Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-259-5438

# Section Quantity:

1

Body Style:

Cylindrical

## **Reliability Indicator:**

Not established

#### **Terminal Length:**

0.187 inches

#### **Body Diameter:**

0.250 inches

Body Length:

#### 0.250 inches

Shaft Bearing Type:

## Sleeve

Actuator Type:

#### Flush drive with slot-hole

#### Effective Electrical Rotation In Deg Angular Rotation:

240.0

#### Maximum Starting Torque:

5.00 inch-ounces

# Maximum Running Torque:

5.00 inch-ounces

# Center To Center Distance Between Terminals:

0.141 inches

## **Terminal Location:**

Rear end

#### Mounting Method:

Terminal

#### Center To Center Distance Between Terminal Rows:

0.071 inches

#### Features Provided:

Hermetically sealed

#### **Electrical Resistance Per Section:**

200.0 kilohms single section

#### Center To Center Distance Between Center Terminal And Outside Terminal:

0.071 inches

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

## Power Dissipation Rating Per Section In Watts:

0.5 free air single section



## **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

## Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0