NSN 5905-01-260-2335

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-260-2335 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.250 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.000 inches **Body Length:** 1.310 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Shaft End Play:**

0.005 inchesShaft Runout:0.002 inches

NSN 5905-01-260-2335

Demilitarization:

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:	
0.002 inches	
Pilot Diameter Runout:	
0.001 inches	
Shaft Radial Play:	
0.001 inches	
Mechanical Backlash In Deg Angular Rotation:	
1.0	
Ferminal Location:	
Radially positioned over less than half the circumference	
Mounting Method:	
Clamp ring	
Electrical Resistance Per Section:	
.0 kilohms single section	
Rotary Actuator Travel In Angular Deg:	
360.0	
Function Conformity Tolerance Per Section:	
0.25/+0.25 single section	
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:	
25.0 single section	
Power Dissipation Rating Per Section In Watts:	
2.0 free air single section	
Function Conformity Per Section:	
Single section independent linearity	
Resistance Tolerance Per Section In Percent:	
10.0/+10.0 single section	
Actuator Travel Control Feature:	
Continuous motion	
Function Characteristic Per Section:	
Single section linear	
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:	
70.0 single section	
Test Data Document:	
81349-mil-r-39023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Ferminal Type And Quantity:	
B turret	
Specification Data:	
31349-mil-r-39023/4 government specification	
Shelf Life:	
N/a	
Jnit Of Measure:	

NSN 5905-01-260-2335

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0