## NSN 5905-01-260-2804



Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5905-01-260-2804 **Section Quantity:** 2 **Body Style:** Rectangular **Reliability Indicator:** Not established **Body Length:** 0.190 inches **Body Width:** 0.480 inches **Body Height:** 0.250 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 

230.0

**Maximum Starting Torque:** 

2.00 inch-ounces

**Maximum Running Torque:** 

2.00 inch-ounces

**Terminal Location:** 

**Dual inline** 

**Mounting Method:** 

**Terminal** 

**Electrical Resistance Per Section:** 

20.0 percent, rated amperes c and better industrial clears

**Rotary Actuator Travel In Angular Deg:** 

230.0

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

0.25 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-20.0/+20.0 all sections

**Actuator Travel Control Feature:** 

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 all sections

**Standard Taper Curve Per Section:** 

A all sections

## NSN 5905-01-260-2804

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
Variable resistor with a dual inline body and two sections
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0