## NSN 5905-01-260-3778

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-260-3778

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -20.0/+20.0   |
| Electrical Resistance:  |
| 86.600 ohms   |
| Resistance Tolerance In Percent:  |
| -3.000/+3.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 25.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 275.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+150.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 1.375 inches and 1.625 inches   |
| Body Diameter:  |
| Between 0.105 inches and 0.125 inches   |
| Body Length:  |
| 0.437 inches  |
| Power Dissipation Rating In Watts:  |
| 0.500 free air  |
| End Application:  |
| F110 engine   |
| Cubic Measure (non-core):   |
| 0.005 cubic inches  |
| Unpackaged Unit Weight:   |
| 0.34 grams  |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 07482-j690 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                           |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5905-01-260-3778

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0