## NSN 5905-01-260-5242

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-260-5242 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.812 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 1.448 inches and 1.466 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.60 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Maximum Stop Torque:** 128.00 inch-ounces **Shaft End Play:** 0.0085 inches **Shaft Runout:** 

0.0005 inches **Lateral Runout:** 0.003 inches **Pilot Diameter Runout:** 0.001 inches **Shaft Radial Play:** 0.003 inches **Fragility Factor:** Moderately rugged

## NSN 5905-01-260-5242

Precision Wire Wound Variable Resistor - Page 2 of 3



Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
1.122 cubic inches
Electrical Resistance Per Section:
20.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Zzzy
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
+0.0/+130.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Special Footuges

Reference Number Differentiating Characteristics:

**Terminal Type And Quantity:** 

3 turret

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Item must comply with requirements of defense supply center columbus production standard no. Lo3788

## NSN 5905-01-260-5242

Precision Wire Wound Variable Resistor - Page 3 of 3



N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0