## NSN 5905-01-260-7669

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-260-7669

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
|--|
| +0.0/+650.0  |
| Electrical Resistance:   |
| 0.100 ohms   |
| Resistance Tolerance In Percent:   |
| -0.500/+0.500  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 25.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 275.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+275.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Established  |
| Reliability Failure Rate Level In Percent:   |
| 0.001  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.078 inches   |
| Body Length:   |
| 0.312 inches   |
| Power Dissipation Rating In Watts:   |
| 1.500 free air   |
| Cubic Measure (non-core):  |
| 0.002 cubic inches   |
| Unpackaged Unit Weight:  |
| 0.3 grams  |
| Style Designator:  |
| Axial terminal each end  |
| Test Data Document:  |
| 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-r-39007/12 government specification  |
| Shelf Life:  |
| N/a  |

--

**Unit Of Measure:** 

## NSN 5905-01-260-7669

Inductive Wire Wound Fixed Resistor - Page 2 of 2



| D   | :1:4. | -:-  | -4:- |     |
|-----|-------|------|------|-----|
| Dem | HIT   | arız | atıc | on: |

No

Fiig:

A001a0