## NSN 5905-01-261-1862

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-261-1862

1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.6250 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.625 inches
Undercut Width:
0.0680 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.124 inches
Shaft Length:
0.318 inches
Body Length:
1.583 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Shaft
Electrical Resistance Per Section:
50.0 kilohms single section
Power Dissipation Rating Per Section In Watts:
3.0 free air single section
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section

**Terminal Type And Quantity:** 

4 tab, solder lug

## NSN 5905-01-261-1862

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0