NSN 5905-01-261-3872

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-261-3872

| view offilite at https://defobasegroup.com/hist//03/05-01-201-3072 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -5.0/+5.0 first temp coefficient |
| Electrical Resistance: |
| 6.500 kilohms |
| Resistance Tolerance In Percent: |
| -0.100/+0.100 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Mil-std-1276 Wire Lead Type Designator: |
| C |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.010 |
| Terminal Length: |
| 1.905 inches |
| Body Length: |
| 0.310 inches |
| Body Width: |
| 0.320 inches |
| Body Height: |
| 0.110 inches |
| Power Dissipation Rating In Watts: |
| 0.300 free air |
| Cubic Measure (non-core): |
| 0.013 cubic inches |
| Unpackaged Unit Weight: |
| 1.000 grams |
| Test Data Document: |
| 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-55182/9 government specification |

N/a

Shelf Life:

NSN 5905-01-261-3872

Film Fixed Resistor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A001a0